

# EUROMASK®

## HIGH TEMPERATURE GREEN TAPE

### Features :

Green Tape is a 90µ PET film with 40µ high performance silicone adhesive. Suitable for all high temperature masking process.

- 204°C resistant
- Powder Coating and Anodizing applications
- Clean removal, no adhesive residue

### Technical Data :

Carrier

Adhesive

Carrier Thickness (mm)

Total Thickness (mm)

Adhesion to Steel (N/25mm – g/25mm)

Tensile Strength (N/25mm – kg/25mm)

Elongation (%)

Dielectric Strength (kV)

Class of Insulation (°C)

Temperature Range (°C)



PET

Silicone

ASTM D 1000	<b>0.05</b>	± 0,003
ASTM D 1000	<b>0.087</b>	± 0,005
ASTM D 1000	<b>11.1 – 1132</b>	± 2,5 - ± 232
ASTM D 1000	<b>216 – 22</b>	± 20 - ± 5
ASTM D 1000	<b>100</b>	± 22
ASTM D 149	<b>6.0</b>	
UL 510	<b>B / 130 UL</b>	
For 60'	<b>-51 to +204</b>	

NOTE: our recommendations are made in good faith and are based on our experience with this product. Since the conditions of use of this product are beyond our control, this data is given on the express condition and understanding that Finishing Group s.r.l. will not be liable to any person by reason thereof. Nothing herein shall be deemed to be a recommendation to use any product in violation of any existing patent right.

FINISHING GROUP S.R.L.