


ZIP 52 Double Diaphragm Pumps



The ZIP 52 pneumatic double diaphragm pumps are designed with a reduction in air consumption coupled with better performance and maximum reliability. The exclusive design enables its use for corrosive, abrasive and highly viscous liquid media. ZIP pumps cover a broad application spectrum, including the feeding of paint supply systems; the feeding and circulation of printing ink, solvents, paints, chemicals, and oils; the disposal of liquid waste; the supply o flow viscosity adhesives; and filling/emptying of tanks, drums and containers. These pumps are offered in aluminum and stainless steel with a volumetric flow of 13.7 gal/min and 1/2" material inlet/outlet size for an extended range of materials.



High efficiency and performance

- The optimized design with less dead space enables rapid color change and cleaning, and a reduction in the amount of solvent required
- The air motor ensures highest performance with reduced air consumption; requires no additional lubrication and suffers from no freezing problems
- Different pump configurations and a comprehensive product palette guarantee a wide range of possible applications

| Technical Data | ZIP 52 |
|--|-------------------|
| Pressure ratio | 1:1 |
| Material pressure | 116 PSI (7.8 bar) |
| Material inlet/outlet | BSP 1/2" |
| Volumetric flow with free drainage 13.7 gal/min | |
| Sound level at max. flow rate and a feed pressure of 116 PSI | 85 dB (A) |

Designed for versatility in application

 The ZIP 52 double diaphragm pumps are available in stainless steel and aluminum models to fit any type of application needs for material supply

Two coupled diaphragms are moving from the left to the right and back by help of pressurized air. The steering valve guides the air to the side where the diaphragm is moved to contract the fluid chamber. Material is transported by contraction and expansion of the fluid chamber volume through the inlet and outlet valves.





ZIP 52 Double Diaphragm Pumps



| ZIP 52 Configurations | | |
|-----------------------|----------------------|---|
| Mount Style | Part Number | Description |
| Bare Aluminum | U550.ATSS7 | Bare aluminum ZIP 52 pump |
| Bare Stainless Steel | U550.STSS7 | Bare stainless steel ZIP 52 pump |
| Cart Mount | ZIP-C5.U550.ATSS7 | Cart mounted ZIP 52 (aluminum) with 5 gallon siphon |
| | ZIP-C55.U550.ATSS7 | Cart mounted ZIP 52 (aluminum) with 55 gallon siphon |
| | ZIP-C5.U550.STSS7 | Cart mounted ZIP 52 (stainless steel) with 5 gallon siphon |
| | ZIP-C55.U550.STSS7 | Cart mounted ZIP 52 (stainless steel) with 55 gallon siphon |
| Wall Mount | ZIP-W5.U550.ATSS7 | Wall mounted ZIP 52 (aluminum) with 5 gallon siphon |
| | ZIP-W55.U550.ATSS7 | Wall mounted ZIP 52 (aluminum) with 55 gallon siphon |
| | ZIP-W5.U550.STSS7 | Wall mounted ZIP 52 (stainless steel) with 5 gallon siphon |
| | ZIP-W55.U550.STSS7 | Wall mounted ZIP 52 (stainless steel) with 55 gallon siphon |
| 5 Gallon Pail Mount | ZIP-P5.U550.ATSS7 | Pail cover mounted ZIP 52 (aluminum) |
| | ZIP-P5A.U550.ATSS7 | Pail cover mounted ZIP 52 with agitator (aluminum) |
| | ZIP-P5.U550.STSS7 | Pail cover mounted ZIP 52 (stainless steel) |
| | ZIP-P5A.U550.STSS7 | Pail cover mounted ZIP 52 with agitator (stainless steel) |
| 55 Gallon Drum Mount | ZIP-DR55.U550.ATSS7 | Drum cover mounted ZIP 52 (aluminum) |
| | ZIP-DR55A.U550.ATSS7 | Drum cover mounted ZIP 52 with agitator (aluminum) |
| | ZIP-DR55.U550.STSS7 | Drum cover mounted ZIP 52 (stainless steel) |
| | ZIP-DR55A.U550.STSS7 | Drum cover mounted ZIP 52 with agitator (stainless steel) |



Cart Mount



Wall Mount



5 Gallon Pail Mount



55 Gallon Drum Mount

WAGNER Systems Inc.

1770 Fernbrook Lane Plymouth, MN 55447 T 800.473.2524 F 630.503.2377

www.wagnersystemsinc.com





